

SPECIFICATIONS

- Contact Configuration:** 3PDT.
- Switch Function:** On-off-on.
- Contact Rating:** 3A 125/250 VAC.
- Contact Resistance:** 20 milli-ohms max.
- Insulation Resistance:** 500 mega-ohms min. at 500VDC.
- Dielectric Strength:** 2,000VAC for 1 minute.
- Life Cycle:** Over 6,000 cycles.
- Operation Force:** 500+/-200g.

MATERIALS

- Actuator:** Type 66 Nylon.
- Base:** Type 66 Nylon.
- Movable Contact:** Silver plated Copper.
- Actuator Tips:** Type 66 Nylon.
- Terminals:** Silver plated Copper.
- Spring:** Stainless Steel wire.

ORDERING INFORMATION

DR-3- 83 [Actuator Marking] - [Housing Color] [Actuator Color]

Actuator Marking:

- A: None
- E: " I O II "

Housing Color:

- B: Black
- W: White
- K: Slate
- L: Light grey
- M: Misty grey

Actuator Color:

- B: Black
- W: White
- K: Slate
- L: Light grey
- M: Misty grey
- R: Red

Part Number: DR-3-83A-BB



Recommended Panel Cutout

| Panel Thickness | X | Y |
|-----------------|-----------|-----------|
| 0.75-1.25 | 19.2-19.1 | 13.0-12.9 |
| 1.25-2.00 | 19.4-19.3 | 13.0-12.9 |
| 2.00-3.00 | 19.8-19.7 | 13.0-12.9 |

